

**MODEL 7150F REDUCING SOCKET ADAPTER (Gr x Ft)
7150M REDUCING NIPPLE (Gr x Mt)
55 NIPPLE ADAPTER (Gr x Mt)**

Shurjoint ductile iron grooved-end fittings are made of ductile iron per ASTM A536 Gr. 65-45-12 and or ASTM A395 Gr. 65-45-15. C-E dimensions are manufacturer's standard.


Shurjoint standard fitting pressure ratings conform to the ratings of Model 7707 couplings.



7150F

7150M


55



For Fire Protection pressure rating, listing, and approval information, refer to Data Sheet B-42 or visit **SHURJOINT** website, www.shurjoint.com for details or contact your **SHURJOINT** Representative.

**MODEL 7150F REDUCING SOCKET ADAPTER (Gr x Ft)
7150M REDUCING NIPPLE (Gr x Mt)**

The **Shurjoint** Models 7150F & 7150M are designed for making direct reduction from a grooved system to female or male threaded system without the need for expensive swaged nipples.



Full warranty terms can be found on www.shurjoint.com


Model 7150F Reducing Socket Adapter, Model 7150M Reducing Nipple											
Nom. Size Gr. X Th.	Pipe O.D.	7150F		7150M		Nom. Size Gr. X Th.	Pipe O.D.	7150F		7150M	
		L	Weight	L	Weight			L	Weight	L	Weight
in	in	in	Lbs	in	Lbs	in	in	in	Lbs	in	Lbs
mm	mm	mm	Kgs	mm	Kgs	mm	mm	mm	Kgs	mm	Kgs
1½ x 1	1.900 x 1.315	2.5	0.60	2.5	0.53	80 x	3.500 x 3.000	2.5	2.20	2.5	2.20
40 x 25	48.3 x 33.4	63.5	0.27	63.5	0.24	76.1mm	88.9 x 76.1	63.5	1.00	63.5	1.00
2 x 1	2.375 x 1.315	2.5	0.92	2.5	0.88	4 x 1¼	4.500 x 1.660	3.0	2.33	3.0	2.19
50 x 25	60.3 x 33.4	63.5	0.42	63.5	0.40	100 x 32	114.3 x 42.2	76.1	1.06	76.1	0.99
2 x 1¼	2.375 x 1.660	2.5	1.01	2.5	0.70	4 x 1½	4.500 x 1.900	3.0	2.05	3.0	2.05
50 x 32	60.3 x 42.2	63.5	0.46	63.5	0.32	100 x 40	114.3 x 48.3	76.1	0.93	76.1	0.93

Model 7150F Reducing Socket Adapter, Model 7150M Reducing Nipple

Nom. Size Gr. X Th.	Pipe O.D.	7150F		7150M		Nom. Size Gr. X Th.	Pipe O.D.	7150F		7150M	
		L	Weight	L	Weight			L	Weight	L	Weight
in	in	in	Lbs	in	Lbs	in	in	in	Lbs	in	Lbs
mm	mm	mm	Kgs	mm	Kgs	mm	mm	mm	Kgs	mm	Kgs
2 x 1½ 50 x 40	2.375 x 1.900 60.3 x 48.3	2.5 63.5	0.95 0.43	2.5 63.5	1.04 0.47	4 x 2 100 x 50	4.500 x 2.375 114.3 x 60.3	3.0 76.1	2.29 1.03	3.0 76.1	2.31 1.05
2½ x 1 65 x 25	2.875 x 1.315 73.0 x 33.4	2.5 63.5	1.21 0.55	2.5 63.5	0.88 0.40	4 x 2½ 100 x 65	4.500 x 2.875 114.3 x 73.0	3.0 76.1	2.25 1.02	3.0 76.1	2.05 0.93
25 x 76.1mm	3.000 x 1.315 76.1 x 33.4	2.5 63.5	1.21 0.55	2.5 63.5	1.64 0.75	4 x 2½ 100 x 65	4.500 x 3.000 114.3 x 76.1	3.0 76.1	2.25 1.02	3.0 76.1	2.05 0.93
2½ x 1¼ 65 x 32	2.875 x 1.660 73.0 x 42.2	2.5 63.5	1.17 0.53	2.5 63.5	1.59 0.72	5 x 1½ 125 x 40	5.563 x 1.900 141.3 x 48.3	3.5 88.9	3.94 1.79	3.5 88.9	2.05 0.93
32 x 76.1mm	3.000 x 1.660 76.1 x 42.2	2.5 63.5	1.17 0.53	2.5 63.5	1.59 0.72	40 x 139.7mm	5.500 x 1.900 139.7 x 48.3	3.5 88.9	3.94 1.79	3.5 88.9	2.05 0.93
2½ x 1½ 65 x 40	2.875 x 1.900 73.0 x 48.3	2.5 63.5	1.08 0.49	2.5 63.5	1.72 0.78	6 x 1½ 150 x 40	6.625 x 1.900 168.3 x 48.3	4.0 101.6	6.47 2.94	4.0 101.6	4.84 2.20
40 x 76.1mm	3.000 x 1.900 76.1 x 48.3	2.5 63.5	1.08 0.49	2.5 63.5	1.72 0.78	40 x 165.1mm	6.500 x 1.900 165.1 x 48.3	4.0 101.6	5.56 2.52	4.0 101.6	4.75 2.15
2½ x 2 65 x 50	2.875 x 2.375 73.0 x 60.3	2.5 63.5	1.52 0.69	2.5 63.5	0.92 0.42	6 x 2 150 x 50	6.625 x 2.375 168.3 x 60.3	4.0 101.6	5.28 2.40	4.0 101.6	4.91 2.23
50 x 76.1mm	3.000 x 2.375 76.1 x 60.3	2.5 63.5	1.52 0.69	2.5 63.5	1.09 0.49	50 x 165.1mm	6.500 x 2.375 165.1 x 60.3	4.0 101.6	5.28 2.40	4.0 101.6	4.91 2.23
3 x 1 80 x 25	3.500 x 1.315 88.9 x 33.4	2.5 63.5	1.91 0.87	2.5 63.5	1.25 0.57	6 x 2½ 150 x 65	6.625 x 2.875 168.3 x 73.0	4.0 101.6	5.46 2.48	4.0 101.6	4.91 2.23
3 x 1¼ 80 x 32	3.500 x 1.660 88.9 x 42.2	2.5 63.5	1.50 0.68	2.5 63.5	1.67 0.76	65 x 165.1mm	6.500 x 3.000 165.1 x 76.1	4.0 101.6	4.40 2.00	4.0 101.6	4.97 2.26
3 x 1½ 80 x 40	3.500 x 1.900 88.9 x 48.3	2.5 63.5	1.63 0.74	2.5 63.5	1.53 0.74	6 x 4 150 x 100	6.625 x 4.500 168.3 x 114.3	4.0 101.6	6.37 2.89	4.0 101.6	4.52 2.10
3 x 2 80 x 50	3.500 x 2.375 88.9 x 60.3	2.5 63.5	1.56 0.71	2.5 63.5	1.32 0.60	100 x 165.1mm	6.500 x 4.500 165.1 x 114.3	4.0 101.6	4.52 2.10	4.0 101.6	4.52 2.10
3 x 2½ 80 x 65	3.500 x 2.875 88.9 x 73.0	2.5 63.5	2.20 1.00	2.5 63.5	2.20 1.00						

MODEL 55 NIPPLE ADAPTER (Gr x Mt)

The **Shurjoint** Model 55 is a cast adapter that allows for a direct transition from grooved system to a male threaded system. For other sizes, see our Model #59 pipe nipples.



10
YEAR
LIMITED
WARRANTY

Full warranty terms
can be found on
www.shurjoint.com

Model 55 Nipple Adapter

Nominal Size Grooves x Threaded	Pipe O.D.	L	Weight
in	in	in	Lbs
mm	mm	mm	Kgs
1½ x 1½M 40 x 40M	1.900 48.3	2.50 63.5	0.77 0.35
2 x 2M 50 x 50M	2.375 60.3	2.50 63.5	0.90 0.40

MATERIAL SPECIFICATIONS

- **Fitting body:**

Ductile Iron to ASTM A536, Gr. 65-45-12 and or ASTM A395,
Gr. 65-45-15, min. tensile strength 65,000 psi (448 MPa).

- **Surface Finish:**

Orange color painted or red RAL3000 color painted.

- Hot dip galvanized. (Option)
- Epoxy coated in red RAL3000 or other colors. (Option)

General Notes:

- **Pressure Ratings** for fittings conform to the working pressure of the coupling used to join the system.
- **Listed and or Approved Pressures** are pressure ratings for fire protection systems, tested and approved by various approval bodies. Please always refer to the latest approval data posted on the **Shurjoint** website.
- **Field Joint Test:** For one time only the system may be tested hydrostatically at 1½ times the maximum working pressure listed (AWWA C606 5.2.3).
- **Warning:** Piping systems must always be depressurized and drained before attempting disassembly and or removal of any components.
- **The 10 Year Limited Warranty** applies to manufacturing defects only and does not cover severe service/temperature applications or wear parts.
- **Shurjoint** reserves the right to change specifications, designs and or standard without notice and without incurring any obligations.

Shurjoint product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact **Shurjoint** Technical Service. **Shurjoint** reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligations to make such changes and modifications on **Shurjoint** products previously subsequently sold.