


MODEL 49 SANDWICH PLATES

The Model #7041, #C341 & #A512 flange adapters require a hard flat surface for effective gasket sealing. A sandwich plate is required and should always be used when the mating surface is not adequate as seen with the serrated faces of some valves or the rubber-faced or rubber-lined flanges of a wafer valve.







Full warranty terms can be found on www.shurjoint.com

MODEL 49 SANDWICH PLATES

	Model #49 for #7041 Flange Adapter		Model #C49 for #C341 Flange Adapter		Model #A49 for #A512 Flange Adapter	
Nominal Size						
	E	D	Е	D	Е	D
in	in	in	in	in	in	in
mm	mm	mm		mm		
2	3.74	2.13	 3.90	2.00	mm	mm
50	95	54	99	51		
21/2	4.65	2.64	4.65	2.50		
∠ 72 65	4.05	2.04 67	4.05	2.30 64		
3	5.12	3.19	5.12	3.00		
3 80	130	81	130	3.00 76		
4	6.22	4.13	6.66	4.00	6.66	4.55
4 100	158	4.13	169	4.00	169	4.55
5	7.40	5.00	7.52	5.00	109	110
5 125	188	128	191	127		
6	8.50	6.10	8.50	6.00	8.50	6.65
150	216	155	216	152	216	169
8	10.67	8.07	210	152		8.80
0 200	271	205			10.63 270	0.00 224
10	12.83	10.15				
250 12	326	258				
	15.00	12.00				
300	381	305				
14	17.40	13.46				
350	442	342				
16	19.92	15.43				
400	506	392				
18	21.26	17.44				
450	540	443				
20	23.50	19.45				
500	597	494				
24	27.87	23.46				
600	708	596				

MODEL 49 MATERIAL SPECIFICATIONS

Material:

Carbon Steel. electro-zinc plated

- □ Stainless steel: 316
- □ Stainless steel: 304.

General Notes:

- Warning: Piping systems must always be depressurized and drained before attempting disassembly and or removal of any components.
- The 10 Year Limited Warranty applies to manufacturing defects only and does not cover severe service/temperature applications or wear parts.
- Shurjoint reserves the right to change specifications, designs and or standard without notice and without incurring any obligations.

V-03-1/1 Rev.J 20160310