

MODEL 117 PAVING BREAKER

PART # 5199 (7/8" HEX x 3-1/4")

PART # 5200 (1" HEX x 4-1/4")



This 30 lb class Paving Breaker is an ideal tool for light to medium demolition work as well as for use in confined areas. This lightweight tool can break up concrete floors, or can be used in any other type of general demolition work.

SPECIFICATIONS

Part #	5199	5200
Chuck Size	7/8" Hex x 3-1/4"	1" Hex x 4-1/4"
Bore Diameter (inches)	1-3/4"	
Stroke (inches)	3-3/8"	
Blows per Minute	1850	
CFM @ 90 psi	34 - 38	
Weight (lbs)	33	
Length (inches)	21-3/4"	
Air Inlet Size	3/8" MALE NPT	

FEATURES

- Patented Automatic Ball Valve
- (Pat. # 8,276,682 B2)
- Drop forged, steel handle
- Built in automatic oiler
- Replaceable chuck bushing
- Rubber handle grips
- Latch type retainer
- Swivel hose connection
- Four bolt back head
- Noise dampening muffler available
- Fitted with Universal hose connector

MODEL 140 PAVING BREAKER

PART # 17923 (1" HEX x 4-1/4")



The Model 140 is a rugged, yet lightweight Paving Breaker designed for light to medium construction work. It is ideally suited for plant maintenance, such as light demolition of floors, pavement, and frozen ground. This tool is also very popular for bridge deck jobs.

SPECIFICATIONS

Part #	17923
Chuck Size	1" Hex x 4-1/4"
Bore Diameter (inches)	1-7/8"
Stroke (inches)	4-1/4"
Blows per Minute	1500
CFM @ 90 psi	48
Weight (lbs)	43
Length (inches)	21-1/8"
Air Inlet Size	1/2" MALE NPT

FEATURES

- Automatic Valve
- Drop forged, steel handle
- Built in automatic oiler
- Rubber handle grips
- Latch type retainer
- Swivel hose connection
- Four bolt back head
- Noise dampening muffler available
- Fitted with Universal hose connector

MODEL 140A AIRGO-LINE® PAVING BREAKER

PART # 18041 (1" HEX x 4-1/4")



The Model 140A *Airgo-Line*® Paving Breaker is a 40 lb class tool. The ergonomically designed handle helps reduce harmful vibration to the hands and arms of the operator. This versatile tool is based on the standard Model 140, the tool being easily converted to the standard handle or ergonomic handle or vice-versa. No power is lost from the standard tool but does increase efficiency and output due to the reduction in operator fatigue.

SPECIFICATIONS

Part #	18041
Chuck Size	1" Hex x 4-1/4"
Bore Diameter (inches)	1-7/8"
Stroke (inches)	4-1/4"
Blows per Minute	1500
CFM @ 90 psi	48
Weight (lbs)	46
Length (inches)	24"
Air Inlet Size	1/2" MALE NPT

FEATURES

- *AIRGO-LINE*® Ergonomic Back Head (interchangeable with standard Back Head) reduces operator fatigue
- Automatic Valve
- Drop forged, steel handle
- Built in automatic oiler
- Rubber handle grips
- Latch type retainer
- Swivel hose connection
- Four bolt back head
- Noise dampening muffler available
- Universal hose connector supplied

MODEL 160 PAVING BREAKER

PART # 5235 (1-1/8" HEX x 6")

PART # 5236 (1-1/4" HEX x 6")



The Model 160, a 60 lb class Paving Breaker, is a hard hitting tool that can be used for medium to heavy demolition work and concrete breaking. The Model 160 is one of the best general purpose breakers around and one of the best tools on the market for asphalt cutting.

SPECIFICATIONS

Part #	5235	5236
Chuck Size (hex)	1-1/8" x 6"	1-1/4" x 6"
Bore Diameter (inches)	2-1/4"	
Stroke (inches)	4-1/8"	
Blows per Minute	1680	
CFM @ 90 psi	60 - 65	
Weight (lbs)	68	
Length (inches)	25-3/4"	
Air Inlet Size	1/2" MALE NPT	

FEATURES

- Patented Automatic Ball Valve (Pat. # 8,276,682 B2)
- Drop forged, steel handle
- Built in automatic oiler
- Rubber handle grips
- Latch type retainer
- Swivel hose connection
- Four bolt back head
- Noise dampening muffler available
- Universal hose connector supplied

MODEL 160A AIRGO-LINE® PAVING BREAKER

PART # 17746 (1-1/8" HEX x 6")

PART # 17747 (1-1/4" HEX x 6")



The Model 160A *Airgo-Line*® Paving Breaker is a 60 lb class tool. The ergonomically designed handle helps reduce harmful vibration to the hands and arms of the operator. This versatile tool is based on the standard Model 160, the tool being easily converted to the standard handle or ergonomic handle or vice-versa. No power is lost from the standard tool but does increase efficiency and output due to the reduction in operator fatigue.

SPECIFICATIONS

Part #	17746	17747
Chuck Size (hex)	1-1/8" x 6"	1-1/4" x 6"
Bore Diameter (inches)	2-1/4"	
Stroke (inches)	4-1/8"	
Blows per Minute	1680	
CFM @ 90 psi	60 - 65	
Weight (lbs)	70	
Length (inches)	28-1/4"	
Air Inlet Size	1/2" MALE NPT	

FEATURES

- *AIRGO-LINE*® Ergonomic Back Head (interchangeable with standard Back Head) reduces operator fatigue
- Patented Automatic Ball Valve (Pat. # 8,276,682 B2)
- Drop forged, steel handle
- Built in automatic oiler
- Rubber handle grips
- Latch type retainer
- Swivel hose connection
- Four bolt back head
- Noise dampening muffler available
- Universal hose connector supplied

MODEL 190 PAVING BREAKER

PART # 5239 (1-1/8" HEX x 6")

PART # 5240 (1-1/4" HEX x 6")



Tough and dependable, the high performance Model 190 Paving Breaker is the most powerful tool American Pneumatic Tools makes. It is designed for big jobs such as heavy demolition and concrete breaking. Since the Model 190 has the ability to penetrate the hardest concrete it is the tool of choice for road building and foundation removal.

SPECIFICATIONS

Part #	5239	5240
Chuck Size (hex)	1-1/8" x 6"	1-1/4" x 6"
Bore Diameter (inches)	2-5/8"	
Stroke (inches)	6-1/8"	
Blows per Minute	1350	
CFM @ 90 psi	75 - 80	
Weight (lbs)	91	
Length (inches)	29"	
Air Inlet Size	3/4" MALE NPT	

FEATURES

- New! Patented Automatic Ball Valve (Pat. # 8,276,682 B2)
- Drop forged, steel handle
- Built in automatic oiler
- Rubber handle grips
- Latch type retainer
- Swivel hose connection
- Four bolt back head
- Noise dampening muffler available
- Universal hose connector supplied

MODEL 190A AIRGO-LINE® PAVING BREAKER

PART # 18618 (1-1/8" HEX x 6")

PART # 18619 (1-1/4" HEX x 6")



The Model 190A *Airgo-Line*® Paving Breaker is a 90 lb class tool. The ergonomically designed handle helps reduce harmful vibration to the hands and arms of the operator. This versatile tool is based on the standard Model 190, the tool being easily converted to the standard handle or ergonomic handle or vice-versa. No power is lost from the standard tool but does increase efficiency and output due to the reduction in operator fatigue.

SPECIFICATIONS

Part #	18618	18619
Chuck Size (hex)	1-1/8" x 6"	1-1/4" x 6"
Bore Diameter (inches)	2-5/8"	
Stroke (inches)	6-1/8"	
Blows per Minute	1350	
CFM @ 90 psi	75 - 80	
Weight (lbs)	90	
Length (inches)	31"	
Air Inlet Size	3/4" MALE NPT	

FEATURES

- *AIRGO-LINE*® Ergonomic Back Head (interchangeable with standard Back Head) reduces operator fatigue
- Patented Automatic Ball Valve (Pat. # 8,276,682 B2)
- Built in automatic oiler
- Rubber handle grips
- Latch type retainer
- Swivel hose connection
- Four bolt back head
- Noise dampening muffler available
- Universal hose connector supplied

AIRGO-LINE® BACK HEAD ASSEMBLIES

FOR PAVING BREAKER MODELS 140A, 160A & 190A



M140A



M160A



M190A

PART # 18034 (140A)
PART # 17684 (160A)
PART # 17720 (190A)

AIRGO-LINE®

Ergonomic Back Head Assemblies are fitted with ergonomically designed handles to help reduce harmful vibrations being transmitted to the hands and arms of the operator. No hitting power is lost from the standard handle tool but they do increase efficiency and output due to the reduction in operator fatigue.

AIRGO-LINE® Ergonomic Back Heads are interchangeable with the standard Back Heads, conversions of tools from standard to ergonomic are done in a matter of minutes.